

Since 1978

SIDEWALK TRIP HAZARDS



- Insurance expenses are already high enough. Don't let a preventable trip and fall happen on your watch. Contact the experts for a quick, professional repair.

Common Causes:

- Tree Roots
- No room for contraction & expansion
- Poor Compaction
- Improper Installation

How can the trip hazards be removed?

- The most common solution is to scarify the existing concrete using a dustless gas powered machine that has special concrete grinders on the bottom. When the machine is pushed over the trip hazard, the concrete is ground down. It typically takes several passes over the area to make the two pieces of concrete level.

Is this a permanent solution?

- If the sidewalk is uneven due to tree roots, they will typically continue to cause problems and the sidewalk will need to be re-scarified again in the future—typically 3 to 5 years.

Is this messy and noisy?

- We use dustless equipment to minimize the mess and the machine is about as loud as a lawnmower. Our tradesmen are trained to leave the jobsite clean and tidy at the end of every work day.

Are there other options?

- Sidewalks can be removed and replaced. This option is often 5 to 7 times more expensive than scarifying. We only recommend this option if it is done in conjunction with root pruning of trees.

*Neat &
Clean*



*Call us NOW
727-584-8001
For a FREE
estimate*

*We Accept
Mastercard
& Visa*

Joswig Construction, Inc has been in business since 1978 - that's over 30 years. We employ only the best, highly skilled craftsmen and our business is focused on concrete - that's all we do, and we are great at it!

Here is a list of some of our satisfied customers:

- **Echelon at Carillon**
Clearwater, FL
- **Linvatec**
Clearwater, FL
- **Hallmark Development**
Clearwater, FL

Joswig Construction, Inc
2150 Lake Ave SE
Largo, FL 33771

Phone: 727-584-8001

Fax: 727-584-7972

Email: concrete@joswigconstruction.com

License CGC-062456

Fully Licensed & Insured